


# Viewing Spool

## Ordering Information

- When ordering, specify material, gauge (if non-standard), dimension and end styles.

- Air flow directional arrow sticker is attached to product.
- Section of acrylic glass with QF ends allowing user to view material flow through ductwork.



Ø in.	Length in.	Std Weight Lbs
3	12.5	2.50
4		3.00
5		3.50
6		4.10
7		4.60
8		5.00
9		5.45
10		6.25
11		7.10
12		8.20
13		11.25
14		14.10
15		18.25
16		22.60
18		18.00

## QF / Flanged Material Options

Galv				SS			
Gauges	Size (in)		Gauges	Size (in)			
	Min. Ø	Max. Ø		Min. Ø	Max. Ø		
Standard	22	3	12	Standard	22	3	12
	20	14	18		20	14	18
Optional	18	4	18	Optional	18	4	18
	16	6	18		16	6	18

### Construction

**Seam:** longitudinal seam is laser welded.

**Collars:** Collars have a laser welded longitudinal seam.

**Acrylic:** Acrylite® - clear, .250 thick

**Optional End Styles:** Standard QF end can be changed to Raw ID (RI), Raw OD (RO), No Fitting (NF), Hose Adapter (RAWFLEX), Flat Flange (FFL), Angle Flange (AFL), or Van Stone (VS).



**Temperature Rating:** Max. temperature limited to 225°F due to properties of the acrylic viewing port.