

## Rigid Flex Steel Hose ◇

### Ordering Information

- When ordering, specify material (galvanized or Stainless Steel), size dimension, end style(s), and length. Supplied in 5' increments.
- Flexible rigid steel hose for higher temperature or abrasive material.
- 1.5" - 6" is sold in 5' increments up to a 25' maximum length. 7" - 14" hoses are sold in 5' increments only. If lengths longer than 5' are needed, Nordfab can supply 5' hose assemblies with Quick-Fit ends to easily connect additional assemblies.
- Raw ends standard. QF or Angle Flange ends can be attached (additional charge).



Size in.	ID in.	Approx. Outside Dia* in.	CL Bend Radius in.	Approx Weight per foot lbs
1.5	1.125	1.75	6.375	1.00
2	2.000	2.25	9.00	1.30
2.5	2.3125	2.75	10.25	1.60
3	3.0625	3.25	12.50	2.00
4	4.000	4.25	16.25	2.60
5	5.000	5.25	19.50	3.00
6	6.000	6.25	25.00	3.60
7	7.250	7.25	27.50	4.00
8	8.125	8.25	32.00	4.60
9	9.125	9.25	34.00	5.30
10	9.750	10.25	37.50	5.90
12	12.000	12.25	44.00	7.00
14	14.000	14.25	53.00	8.10

\*OD varies depending on how hose is wound

◇ Items may take longer than standard lead times.

Do **NOT** use standard SS Hose Clamps with these hoses.



**Temperature Rating:** Galvanized Steel max. 390° F / Stainless Steel max. 1500° F

### Optional End Styles

Standard raw end can be changed to Raw ID, Raw OD, No fitting, Hose Adapter, Flat Flange, or QF (additional cost for hose assembly).

## Ultra Flex Steel Hose ◇

### Ordering Information

- When ordering, specify material (galvanized or Stainless Steel), size dimension, end style(s), and length. Supplied in 5' increments.
- Flexible steel hose for higher temperature or abrasive material.
- 3" - 6" is sold in 5' increments up to a 25' maximum length. 7" - 8" hoses are sold in 5' increments only. If lengths longer than 5' are needed, Nordfab can supply 5' hose assemblies with Quick-Fit ends to easily connect additional assemblies.
- Plain ends standard. QF or Angle Flange ends can be attached (additional charge).



Size in.	ID in.	Approx. Outside Dia* in.	Approx Weight per foot lbs
3	3.036	3.125	2.15
4	4.063	4.250	2.65
5	5.125	5.250	2.95
6	6.063	6.188	3.55
7	7.000	7.250	4.15
8	8.125	8.250	4.55

\*OD varies depending on how hose is wound  
Square lock: ID Tolerance +1/4", -0

Do **NOT** use standard SS Hose Clamps with these hoses.



**Temperature Rating:** Galvanized Steel max. 390° F / Stainless Steel max. 1500° F

### Optional End Styles

Standard raw end can be changed to Raw ID, Raw OD, No fitting, Hose Adapter, Flat Flange, or QF (additional cost for hose assembly).

◇ Items may take longer than standard lead times.

# Flex Hose End Styles

